

**MOBILE PC
WORKSTATIONS
4 TYPES
10 COLOURS**



MASTER CS

TECHNICAL SPECIFICATION

STANDARD MODULE

Safety locks for the drawer and the pair of hinged doors. Dimensions (mm): 791x598x1081 H.





DOOR MODULE

Security lock and polycarbonate glass.
Working dimensions: 655x465 mm H.



Possible addition of a monitor up to 21".
Inside dimensions of the top compartment: 710x530 mm H.

SHUTTER MODULE

Ideal for touch screens.
Usable dimensions: 660x525 mm H.

Security lock and plastic shutter with ergonomic handle

Extensible drawer with keyboard shelf
2 opening locking positions rear space for item storage

Usable dimensions: 655x465 mm H

THE MODULES WITH **DOOR** AND **SHUTTER** ARE DESIGNED TO LET THE MONITOR POWER CABLE THROUGH BY PROVIDING A GAP BETWEEN THE SUPPORT SHELF AND THE REAR WALL.



PERFORATED PANEL MODULE WITH 3 EDGE TOP COVERED IN PVC

Made of sheet steel with holes for tool/Practibox hooks see page 102



MASTER CS



METAL COLOURS



GREY
RAL 7000
.01



GREEN
RAL 6011
.02



BLUE
RAL 5012
.04



GREY
RAL 7035
.08



GREY WHITE
RAL 9002
.1F



RUBY RED
RAL 3003
.1G



GENTIAN BLUE
RAL 5010
.34



PURE WHITE
RAL 9010
.35



ANTHRACITE GREY
RAL 7016
.39



BLUE CAPRI
RAL 5019
.48

PLASTIC parts colour range



CABINET CAPACITY 100 kg



KEY LOCK (KEY)

The cylinder closure "C0" is supplied as standard in cabinets. "C1" or "C2" versions on request. See Master section page 31

KEY



DRAWER CAPACITY



DRAWER EXTENSION



CABINET CLOSER



ALL INDICATED LOAD CAPACITY VALUES ARE NET AND REFER TO EVENLY DISTRIBUTED WEIGHTS

H 1731 mm



ART.				
F AS 1500 10 08	50-75-100	100-96-92%	key	

Standard cabinet with wheels complete with DOOR MODULE with polycarbonate glass, 1 drawer with keyboard shelf, 1 adjustable middle shelf, 1 extensible shelf
Overall dimensions mm 791x598x1735 H

H 1731 mm



ART.				
F AS 1500 20 08	50-75-100	100-96-92%	key	

Standard cabinet with wheels complete with SHUTTER MODULE, 1 drawer with keyboard shelf, 1 adjustable middle shelf, 1 extensible shelf
Overall dimensions mm 791x598x1735 H

H 1104 mm



ART.				
F AS 1400 02 08	50-75-100	100-96-92%	key	

Standard cabinet with wheels, 1 drawer with keyboard shelf, 3-edge top shelf coated in PVC, 1 adjustable middle shelf, 1 extensible shelf
Overall dimensions mm 791x598x1104 H

H 1800 mm



ART.				
F AS 1400 03 08	50-75-100	100-96-92%	key	

Standard cabinet with wheels complete with PERFORATED PANEL, 3-edge top shelf coated in PVC, 1 drawer with keyboard shelf, 1 adjustable middle shelf, 1 extensible shelf
Overall dimensions mm 791x598x1800 H



2 nylon fixed wheels Ø 100 mm
2 nylon swivel wheels with brake Ø 100 mm



ELECTRICAL SYSTEM AND FAN NOT INCLUDED TO COMPLETE YOUR CABINET GO TO PAGE 523



MODULES WITH POLYCARBONATE GLASS DOORS WITH SHUTTER AND PERFORATED PANEL ARE NOT INSTALLED ON STANDARD MODULES. SUPPLIED AS STANDARD WITH FIXING MATERIAL.

MASTER CS

CONFIGURE YOUR CABINET



Drawer equipped with gray RAL 7035 painted top for keyboard.

STANDARD MODULE WITH WHEELS

ART.				
F AS 1400 01 _ _		50-75-100	100-96-92%	key

CABINET WITH HINGED DOORS

Complete with 2 external grids with dust filter, plate with outlet holes for network cables and electrical system cables, side handle, drawer with keyboard shelf, top hole with black plastic cable guide, pair of plates with 2 nylon fixed wheels and 2 nylon swivel wheels with brake Ø 100 mm. Overall dimensions mm 791x598x1081 H Usable dimensions: 663x754 mm H

LOCKS SEE PAGE 31



FLEXIBLE EXTENSIBLE SHELVES

ART.		Usable dim.mm	Front H mm		
M 32 C057 0110 OF _ _		600x447	70	50 - 75 - 100	100% - 96% - 92%



ADJUSTABLE SHELF

ART.		Usable dim.mm	Total H mm	
M 32 PR25 00 0001 _ _		657x478	60	150



MODULES DOORS WITH POLYCARBONATE GLASS WITH SHUTTER AND PERFORATED PANEL DO NOT BE MOUNTED TO THE STANDARD MODULE. SUPPLIED SERIES WITH FIXING MATERIAL.



SHUTTER MODULE

ART.			
F AS 1450 20 _ _		key	

Dimensions: 714x247x650 mm H
Usable dimensions: 655x215x465 mm H
Including with screws for fixing to the standard module



DOOR MODULE WITH POLYCARBONATE GLASS

ART.			
F AS 1450 10 _ _		key	

Dimensions: 714x247x650 mm H
Usable dimensions: 660x215x525 mm H
Including with screws for fixing to the standard module

THE MODULES WITH DOOR AND SHUTTER CAN BE USED INDEPENDENTLY ON WORK BENCHES OR WORK STATIONS.



PERFORATED PANEL

ART.		dim. mm	
M 30 PA71 00 00 00 _ _		708x65x718 H	



ART. M 00 PA71 00 00 F1 00
DRILLED TOP SHELF WITH 3/4 EDGES FOR PERFORATED PANEL FIXING - INCLUDING SCREWS



ART. M 00 T023 AG 00 F1 00
3-EDGE DRILLING FOR CABLE PASSAGE



3-EDGE TOP SHELF

ART.	dim. mm	
M 32 T023 AG 00 31 07	714x573x23 H	

PVC coated shelf. Colour black



Cable length 2 m
Complete with spare plate
galvanised finish

MULTIPLE MOBILE SOCKET, 4 UNIVERSAL SOCKETS, MAX POWER 3680 W

ART.

F AS 4000 01 00

MULTIPLE MOBILE SOCKET 2P + E 16 A 250 V ~

- 4 universal sockets max power 3680 W for:
 - European plugs 2P 2.5 A
 - Italian standard plugs 2P and 2P + E 10 A and 16 A
 - German standard plugs 2P + E 16 A
 - American standard 2P plugs with flat prongs 15 A 125 V non-polarised
 - 2 m of 3G 1 mm cable and plug 2P+T 16 A 250 V ~ German standard (Schuko)
- note: no grounding connection on the 2P + E 16 A 250 V ~ French standard

REGULATORY COMPLIANCE

Standard CEI 23-124

5 OUTLET MULTIPLE MOBILE SOCKET

TYPE AND NUMBER OF WIRED SOCKETS

ART.	D	F	GB	I	CH	IL
F AS 4100 11 00	5	-	-	-	-	-
F AS 4100 21 00	2	3	-	-	-	-
F AS 4100 31 00	2	-	2	-	-	-
F AS 4100 41 00	2	-	-	3	-	-
F AS 4100 51 00	2	-	-	-	3	-
F AS 4100 71 00	2	-	-	-	-	3

MULTIPLE MOBILE SOCKET 220-250V ~ 10A 2P+E:

- 230V~ 10A magnetothermal cutoff switch
- 5 220-250V~ 10A 2P+E sockets (see table)
- 1 220-250V~ 16A 2P+E industrial plug

DEGREE OF PROTECTION IP 30

REGULATORY COMPLIANCE

Standard CEI EN 60204-1:

- equipotential protection circuit continuity applied voltage
- insulation resistance



Cable length 3,5 m
Complete with spare plate
galvanised finish



SPARE PLATE GALVANISED

ART.	dim. mm
F AS 3021 00 99	550x10x67 H



FAN

ART.
F AS 3220 01 00

220V fan wired without grid with Schuko plug



PROFILE

ART.
F AS 4000 PC 07

4-way plastic cable guide, 1000 mm long

